

1.0 LED

LED 7/10W | 350/500mA | 18Vf
COB 3-step | excl. power supply
aluminium powder coated

0.23kg IP20 35°/35° 355° 90° 4-30

87 35°/35° 355° 90° 4-30

	CODE
	112361W
	112361S
	112361G
	112361Q
	112361B

blade springs 89

	CODE
	112361W_C
	112361B_C

Light Colour Selection

	LUMEN	CRI	CODE
2700K	520/710	>90	3
3000K	540/740	>90	5
4000K	580/790	>90	6
1800-2850K	16V 330/450	>95	9

ALWAYS USE

power supply

	CODE
350mA 10W	90223401
500mA 10W	90214404
500mA 15W dim	90224501

more power supplies on page 588



1.0 MR16

QR-CBC51 max.35W | GU5.3
12V | excl. power supply
aluminium powder coated

0.17kg IP20 35°/35° 355° 90° 4-30

87 35°/35° 355° 90° 4-30

	CODE
	112310W0
	112310S0
	112310G0
	112310Q0
	112310B0

blade springs 89

	CODE
	112310W0C
	112310B0C

ALWAYS USE


power supply

	CODE
12V 10W dim	90221401
12V 25W dim	90221701
12V 70W dim	90221904

more specs on page 591

DEEP ADJUST

CEILING RECESSED



1.0 PAR16

PAR16 max.12W | GU10
100-240VAC | 50-60Hz
aluminium powder coated

0.21kg IP20 35°/35° 355° 105° 4-30

87 35°/35° 355° 105° 4-30

	CODE
	112320W0
	112320S0
	112320G0
	112320Q0
	112320B0

blade springs 89

	CODE
	112320W0C
	112320B0C

OPTIONAL

PAR16 LED GU10 7W
phase-cut dim

	CODE
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 593



p. 587