

# FLOS

F015F24B018 Deep Brown


## Mile Wall 2 Washer Down + Asymmetric Up Dimmable 1-10V NEW

Designed by Antonio Citterio



LED - Power LED - 12W - 453+603lm - 2700K - CRI> 80

LED light source included. Integrated 220-240V ON/OFF and 1-10V or DALI dimmable electrical power. Equipped with double cable gland for electrical connection.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Main specifications

|                  |                      |
|------------------|----------------------|
| Mounting         | Wall                 |
| Environments     | Outdoor wet location |
| LED type         | Power LED            |
| Lamp category    | LED                  |
| Number of heads  | 1                    |
| Power (W)        | 12                   |
| System flux (lm) | 453+603              |

### Physical

|                 |            |
|-----------------|------------|
| Colour          | Deep Brown |
| Orientation     | Fixed      |
| Net weight (kg) | 0.8        |
| IP internal     | 65         |

### Download

[Mounting instructions](#) ZIP

### Photometric Files

[LDT / IES](#) ZIP

### Technical Drawings


[2D](#) ZIP

[3D](#) ZIP

[Bim](#) ZIP



## Schematic light drawing



Beam Angle: 57°

| h(m) | E(lx) | D(m)  |
|------|-------|-------|
| 1    | 187   | 4.54  |
| 2    | 47    | 9.08  |
| 3    | 21    | 13.62 |
| 4    | 12    | 18.17 |
| 5    | 7     | 22.71 |

## Photometric


|                    |                  |
|--------------------|------------------|
| Lighting type      | Indirect, Direct |
| Light distribution | Asymmetric       |
| CCT (K)            | 2700             |
| CRI>               | 80               |

## Electrical


|                    |                |
|--------------------|----------------|
| Insulation class   | I              |
| Frequency (Hz)     | 50-60          |
| Main voltage (Vac) | 220-240        |
| Driver             | Integrated     |
| Dimmable           | Yes            |
| Dimming type       | Dimmable 1-10V |
| Emergency type     | No             |

## Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

## Accessories & Power Supply



OPTIONAL  
Accessory

F990E00A000

S.P.D. (SURGE PROTECTION  
DEVICE)