

# FLOS

■ F015F44B030 Black


## Mile Wall 2 Washer Down + Asymmetric Up Dimmable 1-10V NEW

Designed by Antonio Citterio



LED - Power LED - 12W - 489+651lm - 4000K - CRI> 80

LED light source included. Integrated 220-240V ON/OFF and 1-10V or DALI dimmable electrical power. Equipped with double cable gland for electrical connection.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)


### Main specifications

|                  |                      |
|------------------|----------------------|
| Mounting         | Wall                 |
| Environments     | Outdoor wet location |
| LED type         | Power LED            |
| Lamp category    | LED                  |
| Number of heads  | 1                    |
| Power (W)        | 12                   |
| System flux (lm) | 489+651              |

### Physical

|                 |       |
|-----------------|-------|
| Colour          | Black |
| Orientation     | Fixed |
| Net weight (kg) | 0.8   |
| IP internal     | 65    |

### Download


[Mounting instructions](#)  ZIP

### Photometric Files

[LDT / IES](#)  ZIP

### Technical Drawings


[2D](#)  ZIP

[3D](#)  ZIP

[Bim](#)  ZIP



## Schematic light drawing



## Photometric

|                    |                  |
|--------------------|------------------|
| Lighting type      | Indirect, Direct |
| Light distribution | Asymmetric       |
| CCT (K)            | 4000             |
| CRI>               | 80               |

## Electrical

|                    |                |
|--------------------|----------------|
| Insulation class   | I              |
| Frequency (Hz)     | 50-60          |
| Main voltage (Vac) | 220-240        |
| Driver             | Integrated     |
| Dimmable           | Yes            |
| Dimming type       | Dimmable 1-10V |
| Emergency type     | No             |

## Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

## Accessories & Power Supply



OPTIONAL  
Accessory

F990E00A000

S.P.D. (SURGE PROTECTION  
DEVICE)