



PRODUCT SPECIFICATION

GENERAL

FINISH:	Plaster	CABLE LENGTH:	Not Applicable
MAIN MATERIAL:	Plaster	GROSS WEIGHT:	1.02 (kg)
DIMENSIONS:	L: 115mm W: 115mm D: 40mm	CLASS:	CE (Class I)
INSTALLATION ORIENTATION:	Install in to Existing Ceiling	IP RATING:	IP20
CUT OUT HOLE:	L: 150mm W: 150mm	BATHROOM ZONE:	Zone 3
RECESS DEPTH:	140mm/5.51"	VOLTAGE:	Mains 230 (V)
FIRE RATING:	Not Applicable	PRODUCT F MARK:	Not Suitable for: Mounting on flammable materials/Covering with thermal insulation

LAMP

LIGHT SOURCE:	GU10	MACADAM ELIPSE:	Not Applicable
MAXIMUM WATTAGE:	1 x 50W Max	UGR:	To Be Advised
MAXIMUM LAMP LENGTH:	Not Applicable	BEAM ANGLE:	Lamp Dependant
LAMP INCLUDED?	No	TILT ADJUSTMENT ANGLE:	30 (Degrees)
LUMINOUS FLUX:	Lamp Dependant	ROTATION ADJUSTMENT ANGLE:	360 (Degrees)
COLOUR TEMP:	Lamp Dependant	AVERAGE LIFESPAN:	Lamp Dependant
CRI:	Lamp Dependant	L70:	Not Applicable
R9:	Lamp Dependant		

ELECTRICAL

SWITCHED:	Not Applicable	SUPPLY FREQUENCY:	Not Applicable
DIMMABLE:	Yes	DRIVER / BALLAST VOLTAGE:	Not Applicable
DIMMING METHOD:	Lamp Dependant	DRIVER AVERAGE LIFESPAN:	Not Applicable
DRIVER OUTPUT CURRENT:	Not Applicable	EFFICACY:	Lamp Dependant
DRIVER OUTPUT VOLTAGE:	Not Applicable	DRIVER / BALLAST INCLUDED?	Not Applicable

ADDITIONAL INFORMATION



BOX QUANTITY X6

PRODUCT ELEVATIONS

